



BRUTALE RR

ENGINE

Type Three cylinders, 4 stroke, 12 valves
 Timing system "D.O.H.C" with mechanical chain tensioner and DLC tappet

Total displacement 798 cm³ (48.7 cu. in.)
 Compression ratio 13.3:1
 Starting Electric
 Bore x stroke 79 mm x 54.3 mm (3.1 in. x 2.1 in.)
 Max. power - rpm (at the crankshaft) 103 kW (140 hp) at 12.300 rpm
 Max. torque - rpm 87 Nm (8.87 kgm) at 10.250 rpm
 Cooling system Cooling with separated liquid and oil radiators.

Engine management system Integrated ignition - injection system MVICS 2.1 (Motor & Vehicle Integrated Control System) with six injectors. Engine control unit Eldor Nemo 2.1, throttle body bore 50 mm diameters full ride by wire Mikuni, pencil-coil with ion-sensing technology, control of detonation and misfire. Torque control with four maps. Traction control with eight levels of intervention and lean angle sensor.

Electronic quick shift MV EAS 3.0 (Electronically Assisted Shift Up & Down)

Clutch Multi-disk wet clutch with hydraulic actuation and back torque limiting device

Transmission Cassette style; six speed, constant mesh
 Primary drive 22/41

Gear ratio

First gear	13/37
Second gear	16/34
Third gear	18/32
Fourth gear	19/30
Fifth gear	21/30
Sixth gear	22/29

Final drive ratio 16/41

ELECTRICAL EQUIPMENT

Voltage 12 V
 Alternator 350 W at 5.000 rpm
 Battery 12 V - 8.5 Ah

DIMENSIONS AND WEIGHT

Wheelbase 1.400 mm (55.12 in.)
 Overall length 2.045 mm (80.51 in.)
 Overall width 875 mm (34.45 in.)
 Saddle height 830 mm (32.68 in.)
 Min. ground clearance 135 mm (5.31 in.)
 Trail 103.5 mm (4.07 in.)
 Mass in running order (without fuel) 195 kg (429.90 lbs.)
 Fuel tank capacity 16,5 l (4.36 U.S. gal.)

PERFORMANCE

Maximum speed* 244.0 km/h (151.6 mph)
 Acceleration* 0-100 km/h in 3.45 s 0-200 km/h in 9.90 s

FRAME

Type ALS Steel tubular trellis
 Rear swing arm pivot plates material Aluminium alloy

FRONT SUSPENSION

Type Marzocchi "UPSIDE DOWN" telescopic hydraulic fork with DLC treatment, anodized fork legs and rebound-compression damping and spring preload external and separate adjustment
 Fork dia. 43 mm (1.69 in.)
 Wheel travel 125 mm (4.92 in.)

REAR SUSPENSION

Type Progressive, Sachs single shock absorber with rebound and compression damping and spring preload adjustment
 Single sided swing arm material Aluminium alloy
 Wheel travel 130 mm (5.12 in.)

BRAKES

Front brake Double floating disc with Ø 320 mm (Ø 12.6 in.) diameter, with steel braking disc and flange Brembo radial-type monobloc, with 4 pistons Ø 32 mm (Ø 1.26 in.)
 Front brake caliper Single steel disc with Ø 220 mm (Ø 8.66 in.) dia. Brembo with 2 pistons - Ø 34 mm (Ø 1.34 in.) Continental MK100 with RLM (Rear Wheel Lift-up Mitigation) and with cornering function

Rear brake
 Rear brake caliper
 ABS System

WHEELS

Front: Material/size Aluminium alloy 3.50" x 17"
 Rear: Material/size Aluminium alloy 5.50" x 17"

TYRES

Front 120/70 - ZR 17 M/C (58 W)
 Rear 180/55 - ZR 17 M/C (73 W)

FAIRING

Material Thermoplastic

CONTENTS

Exclusive content Steering damper manually adjustable with 8 settings - MV Ride App - GPS sensor - Cruise control - Launch control - FLC (Front Lift Control) - Mobisat anti-theft system with geolocation

OPTIONAL

The full Special Parts range is available on the MV Agusta website

EMISSIONS


Environmental Standard Euro 5
 Combined fuel consumption 5.9 l/100 km
 CO₂ Emissions 138 g/km



SURREAL WHITE (GLOSS)/
 FIRE RED (GLOSS)



FIRE RED (GLOSS)/
 INTENSE BLACK (GLOSS)



* Top speed attained on closed course.

Every country could have a price variation due to local import duties and taxes.

MY 24 - 17/09/24

MV Agusta is committed to the constant improvement of our products. Therefore the information and technical characteristics of the vehicles are subject to change without notice.



BRUTALE RR

ENGINE

Type Three cylinders, 4 stroke, 12 valves
 Timing system "D.O.H.C" with mechanical chain tensioner and DLC tappet

Total displacement 798 cm³ (48.7 cu. in.)
 Compression ratio 13.3:1
 Starting Electric
 Bore x stroke 79 mm x 54.3 mm (3.1 in. x 2.1 in.)
 Max. power - rpm (at the crankshaft) 103 kW (140 hp) at 12.300 rpm
 Max. torque - rpm 87 Nm (8.87 kgm) at 10.250 rpm

Cooling system Cooling with separated liquid and oil radiators.

Engine management system Integrated ignition - injection system MVICS 2.1 (Motor & Vehicle Integrated Control System) with six injectors. Engine control unit Eldor Nemo 2.1, throttle body bore 50 mm diameters full ride by wire Mikuni, pencil-coil with ion-sensing technology, control of detonation and misfire. Torque control with four maps. Traction control with eight levels of intervention and lean angle sensor.

Electronic quick shift MV EAS 3.0 (Electronically Assisted Shift Up & Down)

Clutch Multi-disk wet clutch with hydraulic actuation and back torque limiting device

Transmission Cassette style; six speed, constant mesh
 Primary drive 22/41
 Gear ratio

First gear 13/37
 Second gear 16/34
 Third gear 18/32
 Fourth gear 19/30
 Fifth gear 21/30
 Sixth gear 22/29
 Final drive ratio 16/41

ELECTRICAL EQUIPMENT

Voltage 12 V
 Alternator 350 W at 5.000 rpm
 Battery 12 V - 8.5 Ah

DIMENSIONS AND WEIGHT

Wheelbase 1.400 mm (55.12 in.)
 Overall length 2.045 mm (80.51 in.)
 Overall width 875 mm (34.45 in.)
 Saddle height 830 mm (32.68 in.)
 Min. ground clearance 135 mm (5.31 in.)
 Trail 103.5 mm (4.07 in.)
 Mass in running order (without fuel) 195 kg (429.90 lbs.)
 Fuel tank capacity 16,5 l (4.36 U.S. gal.)

PERFORMANCE

Maximum speed* 244.0 km/h (151.6 mph)
 Acceleration* 0-100 km/h in 3.45 s 0-200 km/h in 9.90 s

FRAME

Type ALS Steel tubular trellis
 Rear swing arm pivot plates material Aluminium alloy

FRONT SUSPENSION

Type Marzocchi "UPSIDE DOWN" telescopic hydraulic fork with DLC treatment, anodized fork legs and rebound-compression damping and spring preload external and separate adjustment
 Fork dia. 43 mm (1.69 in.)
 Wheel travel 125 mm (4.92 in.)

REAR SUSPENSION

Type Progressive, Sachs single shock absorber with rebound and compression damping and spring preload adjustment
 Single sided swing arm material Aluminium alloy
 Wheel travel 130 mm (5.12 in.)

BRAKES

Front brake Double floating disc with Ø 320 mm (Ø 12.6 in.) diameter, with steel braking disc and flange Brembo radial-type monobloc, with 4 pistons Ø 32 mm (Ø 1.26 in.)
 Front brake caliper Single steel disc with Ø 220 mm (Ø 8.66 in.) dia. Brembo with 2 pistons - Ø 34 mm (Ø 1.34 in.) Continental MK100 with RLM (Rear Wheel Lift-up Mitigation) and with cornering function
 Rear brake
 Rear brake caliper
 ABS System

WHEELS

Front: Material/size Aluminium alloy 3.50" x 17"
 Rear: Material/size Aluminium alloy 5.50" x 17"

TYRES

Front 120/70 - ZR 17 M/C (58 W)
 Rear 180/55 - ZR 17 M/C (73 W)

FAIRING

Material Thermoplastic

CONTENTS

Exclusive content Steering damper manually adjustable with 8 settings - MV Ride App - GPS sensor - Cruise control - Launch control - FLC (Front Lift Control) - Mobisat anti-theft system with geolocation

OPTIONAL

The full Special Parts range is available on the MV Agusta website



SURREAL WHITE (GLOSS)/
 FIRE RED (GLOSS)



FIRE RED (GLOSS)/
 INTENSE BLACK (GLOSS)



* Top speed attained on closed course.

Every country could have a price variation due to local import duties and taxes.

MY 24 - 17/09/24 USA

MV Agusta is committed to the constant improvement of our products. Therefore the information and technical characteristics of the vehicles are subject to change without notice.